


(PACLD0006)

DUOLAM 50/50 HOLOGRAPHIC



- Clear 50 PET Film Holographic
- Adhesive HP-2
- Silicone
- Clear 50 PET Film Gloss
- Adhesive V-5
- Silicone
- KW55

Facestocks

- Reference 1: Clear 50 PET Film Holographic
Thickness (μ): 50
Grammage (gr/m²): 70

- Reference 2: Clear 50 PET Film Gloss
Thickness (μ): 50
Grammage (gr/m²): 70

Liner

- Reference: KW55
Description:
Bleached Kraft paper, coated on side and treated on the backside
Thickness (μ): 58
Grammage (gr/m²): 55

Adhesives

- Reference 1: HP-2
Characteristics:
Permanent adhesive hot-melt. Good adhesion to several substrates, specially non-polar ones. Designed with good initial adhesion. Excellent behaviour in machinery and label conversion.

Tack (N) stainless steel FTM-9: > 10
Cohesion (h) 1Kg FTM-8: > 8
Labelling temperature (°C): > 5
Usage temperature (°C): - 5 + 70

- Reference 2: V-5
Characteristics:
Permanent adhesive acrylic water-based. Designed for applications with very high resistance to temperature. Very good performance in converting. Medium initial tack and peel adhesion.

Tack (N) stainless steel FTM-9: > 3
Cohesion (h) 1Kg FTM-8: > 5
Labelling temperature (°C): > 5
Usage temperature (°C): - 10 + 70

DUOLAM 50/50 HOLOGRAPHIC

Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20 °C and 25 °C and a relative humidity of 40-50 %