


(PAOLF0021)

OVERLAM PET 50 HOLOGRAPHIC HP-2 GW60



- Overlam PET Holographic
- Adhesive HP-2
- GW60

● Facestock

Reference: Overlam PET Holographic

Characteristics:

Clear PET film with holographic finishing

Thickness (μ): 50

Grammage (gr/m^2): 70

● Adhesive

Reference: HP-2

Characteristics:

Permanent adhesive hot-melt. Good adhesion to several substrates, specially non-polar ones. Designed with good initial adhesion. Excellent behaviour in machinery and label conversion.

Tack (N) stainless steel FTM-9: > 10

Cohesion (h) 1Kg FTM-8: > 8

Labelling temperature ($^{\circ}\text{C}$): > 5

Usage temperature ($^{\circ}\text{C}$): - 5 + 70

● Liner

Reference: GW60

Description:

Supercalendered glassine white paper, one sided silicone coated

Thickness (μ): 55

Grammage (gr/m^2): 60

Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20 $^{\circ}\text{C}$ and 25 $^{\circ}\text{C}$ and a relative humidity of 40-50 %