


(PATM0004)

## DIRECT THERMAL BOPP 80 WHITE MATT V-10 GW60



- Direct Thermal BOPP White Matt
- Adhesive V-10
- GW60

### ● Facestock

Reference: Direct Thermal BOPP White Matt

Characteristics:

White matt PP film with high thermal sensibility

Thickness ( $\mu$ ): 80

Grammage ( $\text{gr}/\text{m}^2$ ): 70

### ● Adhesive

Reference: V-10

Characteristics:

Permanent adhesive acrylic water-based.

Specially developed for synthetic face materials due to its excellent clarity. Good adhesion to non-polar surfaces.

Tack (N) stainless steel FTM-9:  $> 5$

Cohesion (h) 1Kg FTM-8:  $> 7$

Labelling temperature ( $^{\circ}\text{C}$ ):  $> 5$

Usage temperature ( $^{\circ}\text{C}$ ):  $- 20 + 75$

### ● Liner

Reference: GW60

Description:

Supercalendered glassine white paper, one sided silicone coated

Thickness ( $\mu$ ): 55

Grammage ( $\text{gr}/\text{m}^2$ ): 60

### Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product as well as its printability under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

Exposure to temperatures above  $50^{\circ}\text{C}$  may cause activation of the thermal layer.

### Shelf life

1 year under generally recommended storage at a temperature between  $20^{\circ}\text{C}$  and  $25^{\circ}\text{C}$  and a relative humidity of 40-50 %