


(PATM0009)

MAGNET 200 MG-1 KW110



- Magnet 200
- Adhesive MG-1
- KW110

● Facestock

Reference: Magnet 200

Characteristics:

Magnet for transformation into integrated cards

Thickness (μ): 200

● Adhesive

Reference: MG-1

Characteristics:

Adhesive acrylic solvent based.

Tack (N) stainless steel FTM-9: > 12

Cohesion (h) 1Kg FTM-8: > 24

Labelling temperature ($^{\circ}\text{C}$): > 0

Usage temperature ($^{\circ}\text{C}$): $- 30 + 100$

● Liner

Reference: KW110

Description:

Bleached kraft paper, coated on one side.

Thickness (μ): 105

Grammage (gr/m^2): 110

Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20°C and 25°C and a relative humidity of 40-50 %