


(PATTB0001)

BIADHESIVE FOLDING 280 WHITE RV-4/RV-4 KW80 KW80



- KW80
- Silicone
- Adhesive RV-4
- Folding 280
- Adhesive RV-4
- Silicone
- KW80



Facestock

Reference: Folding 280

Characteristics:

White paper with elemental chlorine free (ECF) cellulose

Grammage (gr/m²): 280

Thickness (µm): 350



Liner

Reference: KW80

Description:

Bleached kraft paper, coated on one side and treated on the other side

Grammage (gr/m²): 80

Thickness (µm): 83



Adhesive

Reference: RV-4

Characteristics:

Semi-removable adhesive acrylic water-based. Designed for applications with very high resistance to temperature. Very good performance in converting. Medium initial tack and peel adhesion.

Tack (N) stainless steel FTM-9: > 1,5

Cohesion (h) 1Kg FTM-8: > 15

Labelling temperature (°C): > 5

Usage temperature (°C): - 20 + 100



Liner

Reference: KW80

Description:

Bleached kraft paper, coated on one side and treated on the other side

Grammage (gr/m²): 80

Thickness (µm): 83

Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product as well as its printability under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20 °C and 25 °C and a relative humidity of 40-50 %