

(PASPM0001) PIN MAILER SHEETS A4 55x30

Sheets

Paper: Offset
not printed or preprinted (1 to 4 colours)

Grammage (gr/m²): 90
can be discussed

Size (mm): 210x297 (A4)
also available in continuous form

Position of the PIN Code Label: freely selectable

PIN Code Label

Frontal

Reference: Polyolefin Laser-Print

Characteristics:
Polyolefin topcoated for laser printing

Thickness (μ): 50

Grammage (gr/m²): 47

Size (mm): 55x30 - printable area approx. 39x19

Adhesive

Reference: HR-1

Characteristics:
Removable adhesive

Tack (N) stainless steel FTM-9: > 6

Labelling temperature (°C): > - 5

Usage temperature (°C): - 15 + 65



Code / PIN label secure



Code / PIN label damaged, partially opened
tamper detection

Additional information

Please visit our PIN mailer solutions website: www.visapin.net

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product as well as its printability under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20 °C and 25 °C and a relative humidity of 40-50 %