

(PASPM0002)
PIN CODE 55x30



- Polyolefin Laser Print
- Adhesive HR-1
- GC60

Facestock

Reference: Polyolefin Laser Print
 Characteristics:
 Polyolefin topcoated for laser printing
 Thickness (μ): 50
 Grammage (gr/m²): 47
 Size (mm): 55x30 - printable area approx. 39x19

Adhesive

Reference: HR-1
 Characteristics:
 Removable adhesive
 Tack (N) stainless steel FTM-9: > 6
 Labelling temperature (°C): > - 5
 Usage temperature (°C): - 15 + 65

Liner

Reference: GC60
 Description:
 Supercalendered glassine cream paper, one sided silicone coated
 Thickness (μ): 55
 Grammage (gr/m²): 60



Code / PIN label secure



Code / PIN label damaged, partially opened
tamper detection

PIN CODE 55x30

Additional information

Please visit our PIN mailer solutions website: www.visapin.net

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product as well as its printability under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20 °C and 25 °C and a relative humidity of 40-50 %