

# (PASPM0008) ULTRA DESTRUCTIBLE PVC 70 WHITE V-4 GW80





Reference: Ultra Destructible White

Characteristics:

White matt vinyl film, highly destructible by delamination.

Thickness (µ): 70

Grammage (gr/m<sup>2</sup>): 135

# Adhesive

Reference: V-4

Characteristics:

Permanent adhesive acrylic solvent-based. High adhesion and cohesion values.

Cohesion (h) 1Kg FTM-8: > 80 Labelling temperature (°C): > 5

Usage temperature (°C): -5 + 40

# Liner

Reference: GW80

Description:

Supercalendered glassine white paper, one sided silicone coated.

Thickness (µ): 70

Grammage (gr/m²): 80

### **Additional information**

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product as well as its printability under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

## Shelf life

6 months under generally recommended storage at a temperature between 20 °C and 25 °C and a relative humidity of 40-50 %