


(PATM0023)
TRIPLEX MAGNET 200
MG-1/RV-2 KW110 PP50



- Clear Gloss Film 50
- Adhesive RV-2
- Magnet 200
- Adhesive MG-1
- Silicone
- KW110

Facestock

- **Reference:** Magnet 200
Characteristics:
 Magnet for the transformation into integrated cards
Thickness (μ): 200

Liners

- **Reference 1:** Clear Gloss Film 50
Description:
 Clear gloss PP film
Grammage (gr/m²): 47
Thickness (μ): 50
- **Reference 2:** KW110
Description:
 Bleached kraft paper, coated on one side and treated on the backside
Grammage (gr/m²): 110
Thickness (μ): 105

Adhesives

- **Reference 1:** RV-2
Characteristics:
 Super removable adhesive acrylic water-based. Adhesive has a low adhesion level which allows easy and clean removal from a wide variety of surfaces.
Tack (N) stainless steel FTM-9: > 1
Cohesion (h) 1Kg FTM-8: > 2
Labelling temperature (°C): > 10
Usage temperature (°C): - 10 + 65
- **Reference 2:** MG-1
Characteristics:
 Adhesive acrylic solvent based.
Tack (N) stainless steel FTM-9: > 12
Cohesion (h) 1Kg FTM-8: > 24
Labelling temperature (°C): > 0
Usage temperature (°C): - 30 + 100

Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product and its printability under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20 °C and 25 °C and a relative humidity of 40-50 %