





# (PATTB0006) TRANSFER TAPE 8/12 GLASSINE 50 HP-5



-  Silicone
-  Transfer Tape
-  Adhesive HP-50

## Facestock

Reference: Transfer Tape

Characteristics:

Carrier free transfer tape, two sided siliconized glassine paper which is overlapping at both edges in order to enable a 'finger-lift' for facile removal.

Thickness ( $\mu$ ): 45

Grammage ( $\text{gr}/\text{m}^2$ ): 50

## Adhesive

Reference: HP-5

Characteristics:

Permanent adhesive hotmelt

Peel Adhesion to steel (24 hour dwell, N/M): 800

Shear Adhesion to steel (1kg; 25mm x 25mm, h): 100

Service temperature range (short term, °C): > 0

Application temperature range (°C): 10 + 50

---

## Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

## Shelf life

1 year under generally recommended storage at a temperature between 20 °C and 25 °C and a relative humidity of 40-50 %