


(PATTB0007)
BIADHESIVE TAPE 6/12
PET 55 V-9/RV-6 GW62



- Adhesive V-9
- Carrier Film
- Adhesive RV-6
- GW62

● **Facestock**

Reference: Carrier Film

Characteristics:

Biadhesive tape with a transparent PET carrier which is overlapping at both edges in order to enable a 'finger-lift' for facile removal.

Thickness (μ): 55 (adhesives included)

Grammage (gr/m²): 61 (adhesives included)

● **Liner**

Reference: GW62

Description:

Glassine white paper, two sided siliconized.

Thickness (μ): 55

Grammage (gr/m²): 62

● **Adhesive**

Reference: V-9

Characteristics:

Permanent synthetic adhesive

Peel Adhesion to steel (24 hour dwell, N/M): 1200

Shear Adhesion to steel (1kg; 25mm x 25mm, h): 100

Service temperature range (short term, °C): > 0

Application temperature range (°C): 10 + 50

● **Adhesive**

Reference: RV-6

Characteristics:

Removable acrylic adhesive

Peel Adhesion to steel (24 hour dwell, N/M): 200

Shear Adhesion to steel (1kg; 25mm x 25mm, h): 2

Service temperature range (short term, °C): > 0

Application temperature range (°C): 10 + 50

Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20 °C and 25 °C and a relative humidity of 40-50 %