


(PAVC0001)

ANTI-GRAFFITI PET 23 V-13 KW125



- Anti-Graffiti PET 23
- Adhesive V-13
- KW125

● Facestock

Reference: Anti-Graffiti PET 23

Characteristics:

Transparent siliconized PET film

Thickness (μ): 23

Grammage (gr/m^2): 32

● Adhesive

Reference: V-13

Characteristics:

Permanent adhesive acrylic water-based. Specially for PVC face materials.

Tack (N) glassl FTM-9: > 3

Peel (N/25mm) glass 24 h. FTM-1: > 10

Labelling temperature ($^{\circ}\text{C}$): > 5

Usage temperature ($^{\circ}\text{C}$): - 20 + 80

● Liner

Reference: KW125

Description:

Bleached kraft paper, coated on one side, treated on the backside.

Thickness (μ): 117

Grammage (gr/m^2): 125

Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20 $^{\circ}\text{C}$ and 25 $^{\circ}\text{C}$ and a relative humidity of 40-50 %