


(PAVC0005)
MONOMERIC PVC 80
WHITE GLOSS RV-3 KW125



- White Gloss PVC
- Adhesive RV-3
- KW125

● **Facestock**

Reference: White Gloss PVC

Characteristics:

White gloss vinyl plasticized film - cadmium free

Thickness (μ): 80

Grammage (gr/m^2): 110

● **Adhesive**

Reference: RV-3

Characteristics:

Super removable adhesive acrylic water-based. Low adhesion level, which enables an easy and clean removal from a wide variety of surfaces.

Tack (N) glas FTM-9: > 1,5

Labelling temperature ($^{\circ}C$): > 5

Usage temperature ($^{\circ}C$): - 5 + 40

● **Liner**

Reference: KW125

Description:

Bleached kraft paper, coated on one side, treated on the backside.

Thickness (μ): 117

Grammage (gr/m^2): 125

Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product as well as its printability under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20 $^{\circ}C$ and 25 $^{\circ}C$ and a relative humidity of 40-50 %