visatac
High-Tech Self-adhesive Materials

(PAVC0007)
CLING-S PET 60 X-1 PET25



- PET 60
- Adhesive X-1
- PET25

Facestock

Reference: PET 60

Characteristics:

Clear PET Cling Tag film

Thickness (µ): 60

Grammage (gr/m²): 84

Adhesive

Reference: X-1

Characteristics:

Silicone adhesive

Peel force (180° on steel, g/inch 20min): 6 ~ 12

Liner

Reference: PET25

Description:

Transparent polyester film, high dimensional stability

Thickness (µ): 25

Grammage (gr/m²): 36

Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product as well as its printability under end use conditions, to determine the suitabiliy for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20 °C and 25 °C and a relative humidity of 40-50 %

VISATAC S.L.
08/2020
info@visatac.com