

(PAVC001 1)

ELECTROSTATIC PVC 145 CLEAR GLOSS CCB180



- Electrostatic PVC Clear Gloss
- CCB180

● Facestock

Reference: Electrostatic PVC Clear Gloss

Characteristics:

Self Cling clear gloss PVC film, contains plasticizer

Thickness (μ): 145

Grammage (gr/m²): 170

● Liner

Reference: CCB180

Description:

White gloss cast coated board

Thickness (μ): 203

Grammage (gr/m²): 180

Application

Self Cling Clear Gloss is easy to apply and sticks without adhesive and can be removed easily without leaving any residue. It is ideal for windows, mirrors and glass and for short time applications where removal or repositioning is a key demand. Printed on the face to apply to the front or even in reverse to apply to the inside of a window facing out.

Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product as well as its printability under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. UV Digital, Solvent Digital, UV Silk-Screen as well as Solvent Silk Screen enable ordinarily a good printability, Offset UV usually a suitable print result. Independently printing tests are required of the customer. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20 °C and 25 °C and a relative humidity of 40-50 %. Properties are influenced by time. For best results printing should be done within 6 months of lamination.