


(PAOLF0047)

JET WB COATED 95 SEMI-GLOSS FSC HP-4 GC60



- Coated Semi-Gloss Paper
- Adhesive HP-4
- GC60

Facestock

Reference: Coated Semi-Gloss Paper

Characteristics:

Coated white semi-gloss woodfree paper special top coated for inkjet water-based printing
FSC™ certified (FSC-MIX Credit AEN-COC-000291)

Thickness (μ): 100

Grammage (gr/m²): 95

Adhesive

Reference: HP-4

Characteristics:

Super permanent adhesive hot-melt. Good adhesion to several substrates, specially non-polar ones. Designed with high initial adhesion. Excellent behaviour in machinery and label conversion. Approved by ISEGA according to the European requirements for direct contact with dry and moist, non-fatty foodstuffs.

Tack (N) stainless steel FTM-9: > 11

Cohesion (h) 1Kg FTM-8: > 6

Labelling temperature (°C): > 0

Usage temperature (°C): - 40 + 60

Liner

Reference: GC60

Description:

Supercalendered glassine cream paper, one sided silicone coated

Thickness (μ): 55

Grammage (gr/m²): 60

Application

This material ensures an outstanding performance and processibility in terms of various scopes of application such as personal care, food, beverages, healthcare and chemical products featuring the chances and benefits of digital printing: On-demand, fast full-color printing of short and ultra short print runs, variable data printing and quick turnarounds.

The facestock provides fast drying, exceptional print definition and density as well as moisture resistance and valueable manageability after the printing process.

Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product as well as its printability under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. The values given are objective, however, some tolerances may appear. This product specification replaces all previous versions. All data is subject to change without prior notice.

Shelf life

1 year under generally recommended storage at a temperature between 20 °C and 25 °C and a relative humidity of 40-50 %



The mark of
responsible forestry