


(PATM0034)

## VELLUM 70 FSC HP-4 GC60



- Vellum 70
- Adhesive HP-4
- GC60

### ● Facestock

Reference: Vellum 70

Characteristics:

White woodfree paper FSC™ certified  
(FSC-MIX Credit AEN-COC-000291)

Thickness (μ): 69

Grammage (gr/m<sup>2</sup>): 70

### ● Adhesive

Reference: HP-4

Characteristics:

Super permanent adhesive hot-melt. Good adhesion to several substrates, specially non-polar ones. Designed with high initial adhesion. Excellent behaviour in machinery and label conversion. Approved by ISEGA according to the European requirements for direct contact with dry and moist, non-fatty foodstuffs.

Tack (N) stainless steel FTM-9: > 11

Cohesion (h) 1Kg FTM-8: > 6

Labelling temperature (°C): > 0

Usage temperature (°C): - 40 + 60

### ● Liner

Reference: GC60

Description:

Supercalendered glassine cream paper, one sided silicone coated

Thickness (μ): 55

Grammage (gr/m<sup>2</sup>): 60

### Additional information

The stated technical specification and information are of a general nature and are based on the experience and on the current knowledge of VISATAC wherefore the suitability of the product for the intended application and the end use cannot be guaranteed. The purchaser of the product is solely responsible to test and to approve the product as well as its printability under end use conditions, to determine the suitability for its purposes and to ensure the product meets the particular requirements. VISATAC cannot be held liable for unsuitable end use of their products. The values given are objective, however, some tolerances may appear. This product specification replaces all previous versions. All data is subject to change without prior notice.

### Shelf life

1 year under generally recommended storage at a temperature between 20 °C and 25 °C and a relative humidity of 40-50 %



The mark of  
responsible forestry